

# TopLifter

## Tailgates By THIEMAN

*Raising Performance to New Levels*

### Model TT-15



Shown with Optional Galvanized Finish and Two-Piece Aluminum Platform

#### FEATURING:

- NEW optional OEM camera/sensor relocation kits available
- Two Piece Bumper (for use with many OEM receivers)
- Reduced Maintenance
- Streamline Design
- Meets TMC Electrical Guidelines
- Direct Dual Cylinder Lift, No Chains or Cables, Wide Opening to Truck Bed
- Heavy-Duty Steel Diamond Plate Platform
- Fully Enclosed Power Unit & Cylinders
- Fast & Easy Installation

The THIEMAN TT Series is completely assembled into one compact unit - ready to run. Simply bolt and/or weld it to the truck and connect the battery cable. Installation is fast and easy. And years from now, it will be just as simple to remount the TT-15 model on a new truck. The lifting mechanism is completely enclosed for a neat appearance and protection from the elements. A two piece bumper, for use with frame attached receivers, is standard on the TT15. The THIEMAN TT's overall design makes it a tough and reliable liftgate.

# Features, Benefits and Specifications



Standard One-Piece Steel Platform with Optional Light Kit



Shown with Optional Two-Piece Alum. Platform

## STANDARD FEATURES AND BENEFITS:

- Dual Cylinder Design for Maximum Lifting Stability.
- Enclosed Cylinders and Power Units for Better Reliability and Easy Accessibility.
- Molded Toggle Switch (Environmentally Sealed).
- Torsion Assist on all 42" Deep Steel and 44" Deep Aluminum Platforms for Easier Opening & Closing of Platform.
- Skid Resistant Steel Diamond Plate Platform for Added Safety.
- Adjustable Cylinder Clevis for Easy Platform and Bed Alignment.
- 150 Amp Circuit Breaker for Electrical Protection.
- Two-Piece Bumper for use with Receivers.

## AVAILABLE OPTIONS FOR TT-15:

- Platform Options Including: Expanded Metal, 2-Piece Folding, Extruded Aluminum, Bar Grate.
- Remote Pendant Control.
- In-Cab Shut Off Switch.
- Light Kit.
- Tire Rack.
- Special Platform Widths and Depths.
- Galvanized Finish.
- OEM Camera/Sensor Relocation Kits.

Model #	Platform	Platform Material	Rated Load Capacity (Lbs.)	Approx. Inst. Wt. (Lbs.)	Bed Height Range
TT15-4926 1PC	49" x 26" + 5"	Steel	1500	500	30" to 45"
TT15-5326 1PC	53" x 26" + 5"	Steel	1500	512	30" to 45"
* TT15-5626 1PC	56" x 26" + 5"	Steel	1500	522	30" to 45"
TT15-4942 2PC	**49" x 42" + 5"	Steel	1500	650	30" to 45"
TT15-5342 2PC	**53" x 42" + 5"	Steel	1500	640	30" to 45"
* TT15-5642 2PC	**56" x 42" + 5"	Steel	1500	670	30" to 45"
TT15-AL-4926 1PC	49" x 26" + 6"	Aluminum	1500	460	30" to 45"
TT15-AL-5326 1PC	53" x 26" + 6"	Aluminum	1500	472	30" to 45"
* TT15-AL-5626 1PC	56" x 26" + 6"	Aluminum	1500	480	30" to 45"
TT15-AL-4932 2PC	**49" x 32" + 6"	Aluminum	1500	480	30" to 45"
TT15-AL-5332 2PC	**53" x 32" + 6"	Aluminum	1500	495	30" to 45"
* TT15-AL-5632 2PC	**56" x 32" + 6"	Aluminum	1500	505	30" to 45"
TT15-AL-4944 2PC	**49" x 44" + 6"	Aluminum	1500	525	30" to 45"
TT15-AL-5344 2PC	**53" x 44" + 6"	Aluminum	1500	535	30" to 45"
* TT15-AL-5644 2PC	**56" x 44" + 6"	Aluminum	1500	550	30" to 45"

\*Installation Kit NOT Included (Installation Kit Must Be Ordered Separately for Models with 56" Wide Platforms).

\*\*Two-Piece Platform (2PC)

TT15-49" x 26"/49" x 32"/49" x 42"/49" x 44"..... Utility and Service Bodies (Liftgate Frame Dimensions: Post OD=55.00, Post ID=48.62)

TT15-53" x 26"/53" x 32"/53" x 42"/53" x 44"..... Utility and Service Bodies (Liftgate Frame Dimensions: Post OD=59.00, Post ID=52.62)

TT15-56" x 26"/56" x 32"/56" x 42"/56" x 44"..... 1988 and Later GMC/Chevrolet Pickup, 1994 and Later Dodge Pickup, 1997 and Later Ford Pickup

Distributed By:



*Raising Performance to New Levels*

600 East Wayne Street  
 Celina, Ohio 45822  
 Phone: 419-586-7727 or  
 800-524-5210  
 Fax: 419-586-9724  
[www.thiemantailgates.com](http://www.thiemantailgates.com)  
[info@thiemantailgates.com](mailto:info@thiemantailgates.com)

THIEMAN Reserves the right to Change Products Specifications at any time Without Prior Notice.  
 Printed in U.S.A. Rev. 2/20 • 2M • MP102426