

MDL SERIES RAIL GATE



MEDIUM DUTY

1,250 lb. - 3,000 lb. Capacities

CHAIN AND SPROCKET DRIVE OFFERS WEIGHT SAVINGS, REDUCED MAINTENANCE, AND GREATER LOAD STABILITY OVER COMPETITIVE ARCING DESIGN.

*Products shown may feature optional equipment.
Content subject to change without notice.*

Optional aluminum platform shown



STANDARD MDL SERIES ADVANTAGES INCLUDE:

- Applications - straight trucks, cube, cutaway, or step vans, flat beds, and dual wheel service bodies.
- Level ride lift - maximum load stability, with straight vertical platform movement.
- Standard steel, anti-skid treadplate platform and ramp for better grip - available with aluminum platform up to 60" deep (larger platforms available by special request).
- Anti-skid treadplate platform and ramp for better grip.
- Compact, weight saving design increases payload and fuel efficiency.
- Built-in toe deflector.
- UHMW Lifetime Warranty Slide Pads on runners.
- Power unit installed, tested, and enclosed in weather protected housing.
- Charge line circuit protection.
- Torsion bar assisted platform makes it easier to open and close.
- Meets TMC specifications.
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion.
- Factory installed cycle counter.
- Built-in 6 LED Light Kit.
- Dedicated Ground.

Easier handling of wheeled carts, bins and racks with this level-ride platform liftgate.



Above-Floor Option shown



MDL Series Gate in stowed position



Designed Simplicity - Maximum Performance

www.waltco.com

MDL SERIES MEDIUM DUTY

RAIL GATE

SPECIFICATIONS:

Bed Ht: 30"-56"



Aluminum Ramp Shown

Model	Capacity	Platform	Ramp	Weight
*MDL-12	1,250 lbs.	30" x 89"	6"	492 lbs.
*MDL-12	1,250 lbs.	36" x 89"	6"	526 lbs.
MDL-16	1,600 lbs.	36" x 89"	6"	568 lbs.
MDL-20	2,000 lbs.	36" x 89"	6"	568 lbs.
MDL-20	2,000 lbs.	42" x 89"	6"	601 lbs.
MDL-30	3,000 lbs.	36" x 89"	6"	679 lbs.
MDL-30	3,000 lbs.	42" x 89"	6"	724 lbs.
MDL-30	3,000 lbs.	48" x 89"	6"	771 lbs.
AP (Aluminum Platform)				
MDL/AP-12	1,250 lbs.	30" x 89"	6"	458 lbs.
MDL/AP-12	1,250 lbs.	36" x 89"	6"	482 lbs.
MDL/AP-16	1,600 lbs.	36" x 89"	6"	524 lbs.
MDL/AP-16	1,600 lbs.	42" x 89"	6"	549 lbs.
MDL/AP-16	1,600 lbs.	48" x 89"	6"	573 lbs.
MDL/AP-16	1,600 lbs.	54" x 89"	6"	598 lbs.
MDL/AP-16	1,600 lbs.	60" x 89"	6"	623 lbs.
MDL/AP-16	2,000 lbs.	36" x 89"	6"	524 lbs.
MDL/AP-20	2,000 lbs.	42" x 89"	6"	549 lbs.
MDL/AP-20	2,000 lbs.	48" x 89"	6"	573 lbs.
MDL/AP-20	2,000 lbs.	54" x 89"	6"	598 lbs.
MDL/AP-20	2,000 lbs.	60" x 89"	6"	623 lbs.
MDL/AP-20	3,000 lbs.	36" x 89"	6"	582 lbs.
MDL/AP-30	3,000 lbs.	42" x 89"	6"	607 lbs.
MDL/AP-30	3,000 lbs.	48" x 89"	6"	631 lbs.

Notes: Above floor models are available for 30"-47" bed heights with a maximum above floor travel of 11".

*MDL-12 models are available with a bed height range of 30"-46"

OPTIONAL EQUIPMENT:

- Above Floor Travel.
- Deeper, narrower, or wider platforms available.
- Hydraulic controlled close (not available on MDL-12).
- Oversized ramp - fixed, hinged, or with cart stop in aluminum or steel.
- Remote hand held toggle switch control with 15 ft coil cord.
- Platform material options:
 - Aluminum
 - Bar Grating
- Custom Options - Contact Factory.
- Galvanized Option (requires aluminum platform).
- 102" Wide Platform.
- 12" Fixed Ramp with cart stops.

Waltco Lift Corp.
 Corporate Office United States
 1777 Miller Parkway
 Streetsboro, OH 44241
 P: 330.633.9191
 F: 330.633.1418
 Waltco.com

Waltco Sales
 T: 800.211.3074
 F: 800.211.3075
 Email: sales@waltco.com

